



PROJECT SUBMITTAL

Project _____ Date _____

Engineer / Architect _____

Builder / Developer _____

Plumbing Contractor _____

Fluidmaster Part Number(s) _____

Fluidmaster Toilet Water Supply Connectors

Connector Sizes and Lengths (in inches)

Toilet Connectors	Vinyl	SS	Available Lengths	Qty.
3/8" Comp., 7/16" Comp., 1/2" Comp., or 1/2" F.I.P. x 7/8" Ballcock	N/A		9" 12" 16" 20"	
3/8" Comp. x 7/8" Ballcock			6" 9" 12" 16" 20"	
1/2" Comp. x 7/8" Ballcock	N/A		9" 12" 16" 20"	
1/2" F.I.P. x 7/8" Ballcock			9" 12" 16" 20"	

Toilet Click Seal™ Connectors	Vinyl	SS	Available Lengths	Qty.
3/8" Comp., 7/16" Comp., 1/2" Comp., or 1/2" F.I.P. x 7/8" Ballcock	N/A		9" 12" 20"	
3/8" Comp. x 7/8" Ballcock	N/A		9" 12" 16" 20"	

Materials of Construction*:

Braid	304 Series Stainless Steel
Internal Hose	Polyvinyl Chloride (PVC)
Hose (<i>Vinyl Version only</i>)	Polyvinyl Chloride (PVC) Reinforced Vinyl
Plastic Coupling Nut	Glass Filled Polypropylene
Metal Nuts	Nickel Plated Brass Alloy
Ferrule	Nickel Plated Brass Alloy
Washer	Santoprene™
Nipple	Brass Alloy

**All connectors are lead free and contain a weighted average lead content of ≤ 0.25%.*

Technical Specifications

Flow Rate	7.18 to 7.26 GPM @ 80 PSI
Working Pressure	125 PSI
Working Temperature	40° F to 150° F

Plumbing Codes

IAPMO Uniform Plumbing Code
IPC International Plumbing Code
NPCC National Plumbing Code of Canada

Standards

ASME A112.18.6 / CSA B125.6
NSF Standard 61, Section 9